

34 parameters

WBC, LYM%, MON%, NEU%, EOS%, BAS%, LYM#, MON#, NEU#, EOS#, BAS#, RBC, HGB, HCT, MCV, MCH, MCHC, RDW_CV, RDW_SD, PLT, MPV, PDW, PCT, P_LCR, P_LCC, RETIC%, RETIC_ABS, IRF

6 research parameters: ALY#, ALY%, LIC#, LIC%, NRBC#, NRBC%

2 histograms for RBC and PLT

2 scatter grams: 5-part differential scatter gram

Eosinophils and Neutrophils scatter gram

Principles of operation

WBC/DIFF: flow cytometry, semi-conductor laser light multi-dimensional cell classification

WBC analysis: optical and impedance measurements

RBC/PLT analysis: impedance method

HGB test: cyanide-free reagent colorimetry

Reagent

Diluent, detergent, lyse, sheath

Sampling modes & aspiration volume

Whole blood: 20 µL, pre-diluent: 20 µL

Aperture diameter

WBC 100 µm, RBC/PLT 68 µm

Throughput

Whole blood: up to 60 samples per hour, pre-diluent: up to 60 samples per hour

Data storage

Up to 200,000 sample results with grams

Alarms

Error messages & pathological flagging

Display

10.4-inch color touch screen

Power

AC 100–240V, 50/60Hz, 250VA

Dimension

490 mm (L) x 459 mm (W) x 332mm (H)

Weight

About 35 kg

URIT Since 1984
Global Diagnostics Supplier



URIT-5160

5-Part-Diff Hematology Analyzer

34 Parameters including RETIC_ABS, RETIC%, IRF

Flow Cytometry (FCM) + Multi Angle Scatter Separation (MASS)

Hourly throughput up to 60 samples

Resistant RBC mode

Multi-language software available (Tailor-Made)



URIT Medical Electronic Co., Ltd.

Head Office

Add.: No. D-07 Information Industry
District, High-tech Zone, Guilin, Guangxi, 541004, P.R. China
Tel: +86-773-2288586 Fax: +86-773-2288560
E-mail: export@uritest.com service@uritest.com
http://www.urit.com

Shenzhen Office

Add.: Room EJ, 24th Floor, New Baohui Building, Nanhui Road,
Nanshan District, Shenzhen, P.R. China
Tel: +86-755-26413721
Rev: 201908-3 (20190815)



Guilin, China



URIT-5160

- Reticulocyte test: RETIC_ABS, RETIC%, IRF
- 34 parameters, 2 histograms, 2 scatter grams
- Hourly throughput up to 60 samples
- Minimized design of 5-part
- The combination of WIC and WOC for WBC counting
- Impedance method for RBC and PLT counting
- Cyanide free reagent for hemoglobin counting
- On board storage capacity of 200,000 samples with all grams
- Support variety of external color printers
- LIS and HIS available with HL7 protocol



Laser Scatter

- Multi-angle scatter separation (MASS)
- Original cell morphology signal
- Stable and long-lasting




Sheath Flow Regulation

- Chemical dye free technology
- Only sheath reagent for WBC 5-diff



Diluting Unit

- Separation system for motors and syringes
- Ceramic syringes
- High precision motors



Electronic and Mechanical Components

- Individual quality control management
- Military level
- 20 years field-proven



2D Grams

- Two 2D histograms: RBC and PLT
- Two 2D scattergrams: 5-part differential Eosinophil and Neutrophil



Data Management

- On board storage capacity of 200,000 sample results
- Professional data statistics query system



Operation Interface

- Simple touch operation with user friendly illustrated icons
- Handy tool tips
- Unique Urit operation interface like all Urit hematology series



Quality Control Solution

- Urit original QC reagent with multi-method as L-J, X-R, X-B, etc.
- Third party QC solution available